

MX-500KG

AMX SERIES

Plastic mixer

塑料混色机系列

Description:

AMX series spiral mixers are suitable for granules, solid plsatic material and color masterbatch mixing. This machines are a kind of large plastic color mixer.It is better than the traditional plastic color mixer with some defects. And also, it is characterized of large mixing capacity, low energy consumption and high efficiency. It is widely used for plastic extrusion, injection processing.

AMX系列螺旋式混料机适用于各种粒状固态塑胶原料及色母之搅拌及混色, 本机是塑料混合大型设备, 它克服了传统混料机各种混合缺陷与弊端, 它具有容量 大,能耗少,加工效率高等优点,是塑料挤出、注射加工生产理想的辅助设备。

Close-up 特写




▶ Screw Type Mixing Part

- 螺旋叶焊接后整体加工,同心度高,运行平稳;
- 螺旋循环搅拌使得原料混合更加均匀、快速;
- 设备与原料所接触部分的材料皆为不锈钢制作,清洗容易;
- 马力小,混合量大,速度快,密封式搅拌,混料均匀,绝无漏 料:
- 自动停止装置,可自由设定所需时间,方便耐用;
- 电机设过载荷保护,保护电机安全;
- 出料口配配手动关料板,下料方便。

- Spiral leaf need to be welded before processing in order to shaft concentrictly and
- Materials in the tank can be round stirred like swirl to decrease mixing time and mix evenly.
- The machines surface made of stainless where will be touched the equipment and raw materials in order to clean easily and avoid rustiness
- Lower power,large mixing capacity,sealed mixing,mixed evenly in short time,no
- Auto-stop device, the setting range for auto-stop is up to your choice, easy and
- Overload protector for motor and interlock protection device, double protection for the safety of workers and motor:
- Equiped with hand-operated cut-off plate for discharge port, easy for discharging.







▶ Specifications 规格表

| 机型 Model | | 小型混色机 small capacity plastic mixer | | | 大型混色机 large capacity plastic mixer | | | |
|--------------------------|----|---------------------------------------|---------|----------|---------------------------------------|-----------|-----------|------------|
| | | | AMX-80L | AMX-160L | AMX-260L | AMX-500KG | AMX-600KG | AMX-1000KG |
| 电机功率 Power | | kw | 0.37 | 0.55 | 1.1 | 2.2 | 2.2 | 4.0 |
| 混合量 Mixing capacity | | kg/min | 50/5 | 100/5 | 150/5 | 500/10 | 600/10 | 1000/10 |
| 主轴转速 Rotor speed | | rpm | 210 | 210 | 210 | 420 | 420 | 420 |
| 加热系统 With heating system | -H | | | | | | | |
| 重量 Weight | | kg | 55 | 100 | 150 | 360 | 400 | 550 |
| 外形尺寸 External size | | | | | | | | |
| L | | mm | 770 | 940 | 1000 | 1430 | 1430 | 1500 |
| W | | mm | 660 | 815 | 880 | 1240 | 1240 | 1400 |
| Н | | mm | 1130 | 1320 | 1485 | 2570 | 2670 | 3020 |

产品规格若有变更,恕不另行通知。Please excuse for not note if some specifications of products are changed.

Note 注: 1) " ("is selection purchase, 2)In general, the mixing time is 5-10 minutes. 3)The standard power voltage is 3φ 380V 50Hz; other voltage is available.

1)"○"为选购件。 2)一般混料时间为5-10分钟。 3)机器电压规格为3 o 380V 50Hz。